

CONDUT S Y S T E M PIPES, FITTINGS & ACCESSORIES

Sustainable Solutions for Your Valuable Projects









INTRODUCTION

SHIELD is a company created to cater to the infrastructure, fire protection and building services industries with a comprehensive range of products designed to be competitive and of assured quality.

We stay ahead of today's evolving market requirements by committing to a program of continued research and development.

We are able to maintain our high standards by ensuring that our worldwide manufacturing networks are the most advanced in the industry in Europe, Asia and America in terms of quality and delivery lead time. Our fully experienced and professional staff is there to provide engineering expertise and after sales service exactly when you need it.

Combine this with highly responsive and customer focused network of distribution centres around the world, you will find that customer satisfaction is what we excel at.

We are justifiably proud of our global client base. With offices and facilities in the UK and Middle East, we are able to comprehend the specific needs of your particular region.



TABLE OF CONTENTS

1 —	Steel lubes
1 1	BS 4568 Conduit BS 31 Conduit
2 —	Bending Machine & Accessories
4 - 12 ——	Fittings & Accessories
4 6 8 8 9 9 10 11	Box-Circular, Small Box-Circular, Large Looping in Box Small Extension Pattern Box Small Box Cover (lids) Hook & Loop Coupling, Elbow, Bend and Tee Bush, Ring, Plug & Gland and Reducer Locknut and Saddle
13 - 14 ——	Switch & Socket Boxes
13 14 14	Galvanized Gang Box Adaptable Box PVC Gang Box
15 —	Support Channel & Accessories
15 15 15 15	Plain Support Channel Slotted Support Channel Channel Nut Threaded Rod
16 - 17 ——	Flexible Steel Conduits
16 17	Flexible Steel Conduit PVC Coated Flexible Steel Conduit
18 - 19 ——	Flexible Conduit Connectors
18 18 19 19	Flexible Conduit Connector (DPJ Type) Two Piece Connector Flexible Conduit Connector 45°/90° (DNJ/DWJ Type) One Piece Connector
21 - 22 ——	PVC Conduits
21 21 22 22	PVC Rigid Conduit PVC Accessories PVC Junction Box PVC Adaptable Box PVC Switch/Socket Cover



SHELD CONDUIT SYSTEM



Steel Tubes

BS 4568 Conduit:

SD-CP


Size	Outside Dia	meter (O.D.)	Wall Thickness	Length	Length o	f Thread
	Min	Max			Min	Max
mm	mm	mm	mm	meter	mm	mm
Heavy Gauge						
16	15.7	16.00	1.40	3.75	11.5	13.5
20	19.7	20.00	1.60	3.75	13.0	15.0
25	24.6	25.00	1.60	3.75	16.0	18.0
32	31.6	32.00	1.60	3.75	18.0	20.0
40	39.6	40.00	1.80	3.75	19.0	22.0
50	49.6	50.00	1.80	3.75	19.0	22.0
Medium Gauge						
16	15.7	16.00	1.35	3.75	11.5	13.5
20	19.7	20.00	1.35	3.75	13.0	15.0
25	24.7	25.00	1.35	3.75	16.0	18.0
32	31.7	32.00	1.35	3.75	18.0	20.0
Light Gauge						
16	15.7	16.00	1.00	3.75	11.5	13.5
20	19.7	20.00	1.00	3.75	13.0	15.0
25	24.6	25.00	1.00	3.75	16.0	18.0
32	31.6	32.00	1.00	3.75	18.0	20.0

BS 31 Conduit:


SD-CP

Size	Outside Diameter (O.D.)		Wall Thickness	Length	Length o	of Thread
	Min	Max			Min	Max
Inch	mm	mm	mm	meter	mm	mm
Heavy Gauge						
3/4	18.90	19.05	1.60	3.81	11.5	13.5
1	25.25	25.40	1.60	3.81	13.0	15.0
11/4	31.50	31.80	1.60	3.81	16.0	18.0
11/2	37.80	38.10	1.80	3.81	18.0	20.0
2	50.50	50.80	1.80	3.81	19.0	22.0
21/2	63.20	63.50	2.00	3.81	19.0	22.0
Medium Gauge						
3/4	18.90	19.05	1.35	3.81	11.5	13.5
1	25.25	25.40	1.35	3.81	13.0	15.0
11/4	31.50	31.80	1.35	3.81	16.0	18.0
11/2	37.80	38.10	1.35	3.81	18.0	20.0
2	50.50	50.80	1.35	3.81	20.0	23.0
21/2	63.20	63.50	1.35	3.81	24.0	28.0
Light Gauge						
3/4	18.90	19.05	1.20	3.81	11.5	13.5
1	25.20	25.40	1.20	3.81	13.0	15.0
11/4	31.50	31.80	1.20	3.81	16.0	18.0
11/2	37.80	38.10	1.60	3.81	19.0	20.0
2	50.40	50.60	1.60	3.81	19.0	23.0
21/2	63.20	63.50	1.60	3.81	24.0	28.0

CLASS 3




CLASS 4





Bending Machine & Accessories











Malleable Iron Junction

boxes for electrical wiring



The complete range of Conduit, Fittings and Accessories for strong, durable & safe wiring system.

Box Circular, Small:

Materials: Malleable Iron

Finish: Galvanized

Size: 60.3 mm Internal Diameter

20mm Boxes: min. 25mm deep

25mm Boxes: min. 28mm deep

Specifications:

- ▶ Tapped M4 at 50.8mm centres
- ▶ With tapped hole in base for earthing screw
- ▶ Supplied without cover or fixing screws unless ordered.



Terminal (1 Way)

SD-C1JB

BS 4568 Size: 20mm 25mm BS 31 Size: 3/4" 1"



Through (2 Way)

SD-C2TJB

BS 4568 Size: 20mm 25mm BS 31 Size: 3/4" 1"



Angle (A Way)

SD-C2AJB

BS 4568 Size: 20mm 25mm BS 31 Size: 3/4"



Tee (3 Way)

SD-C3TJB

BS 4568 Size: 20mm 25mm BS 31 Size:



Intersection (4 Way)

SD-C4WJB

BS 4568 Size: 20mm 25mm BS 31 Size: 3/4"



Back Outlet

SD-CBOJB

BS 4568 Size: 20mm 25mm



Terminal and Back Outlet

SD-C1TBOJB

BS 4568 Size: 20mm 25mm



Through and Back Outlet

SD-C2TBOJB

BS 4568 Size: 20mm 25mm







Angle and Back Outlet SD-C2ABOJB BS 4568 Size: 20mm 25mm



Tee and Back Outlet SD-C3TBOJB BS 4568 Size: 20mm 25mm




Intersection and Back Outlet SD-C4WBOJB BS 4568 Size: 20mm 25mm



Tangent Through SD-C2TTJB BS 4568 Size: 20mm 25mm



Tangent Angle SD-C2TAJB BS 4568 Size: 20mm 25mm



Tangent Tee SD-C3TTJB BS 4568 Size: 20mm 25mm



Branch 3 Way (Y) SD-CB3WJB BS 4568 Size: 20mm 25mm 32mm



Branch 2 Way (U) SD-CB2WJB BS 4568 Size: 20mm 25mm 32mm

20mm 25mm 32mm



Box Circular, Large:

Materials: Malleable Iron

Finish: Black Enamel & Galvanized

Size: 81 mm Internal Diameter

32mm Boxes: min. 38mm deep



Terminal (1 Way)

SD-C1LJB

BS 4568 Size: 32mm



▶ Tapped M4 at 71.5mm centres

▶ With tapped hole in base for earthing screw

▶ Supplied without cover or fixing screws unless ordered.

Specifications:

Tee

SD-C3TLJB

BS 4568 Size: 32mm

BS 31 Size:



Angle SD-C2ALJB

BS 4568 Size: 32mm



Back Outlet

SD-CBOLJB

BS 4568 Size: 32mm



Intersection

SD-C4WLJB

BS 4568 Size:



Through & Back Outlet

SD-C2TBOLJB

BS 4568 Size: 32mm



Terminal and Back Outlet

32mm

SD-C1TBOLJB

BS 4568 Size: 32mm



Through SD-C2TLJB

BS 4568 Size: 32mm







Angle & Back Outlet SD-C2ABOLJB BS 4568 Size: 32mm




Tee and Back Outlet SD-C3TBOLJB BS 4568 Size: 20mm



Intersection and Back Outlet SD-C4WBOLJB BS 4568 Size: 20mm



Tangent AngleSD-C2TALJB
BS 4568 Size: 20mm



Tangent TeeSD-C3TTLJB
BS 4568 Size: 20mm



Looping in Box:

Specifications:

- ▶ With tapped hole in base of earthing screw
- ▶ 20mm clearance





Steel Medium

SD-C1HLB-S & SD-C4HLB-S


Material: Steel

Finish: Galvanized

Size: 29mm Deep x 63.5mm I.D.

With tapped hole in base for earthing screw. 1 hole or 4 knockouts.





SD-C1HLB, SD-C2HLB, SD-C3HLB & SD-C4HLB

Material: Malleable Iron
Finish: Galvanized

Size: 31mm Deep x 63.5mm I.D.

With tapped hole in base for earthing screw. 1, 2, 3 & 4 holes.

Small Extension Pattern Box:

Materials: Malleable Iron

Finish: Galvanized

20mm/25mm Boxes: min. 25mm deep

Size: 60.3mm Internal Diameter





Specifications:

- ▶ Tapped M4 at 50.8mm centres
- ▶ With tapped hole in base for earthing screw
- ▶ Supplied without cover or fixing screws unless ordered.



Terminal SD-C1PB

Size: 20mm 25mm





Angle

SD-C2APB

Size: 20mm 25mm



Through SD-C2TPB

Size: 20mm 25mm



Intersection SD-C4WPB

Size: 20mm 25mm



Tee SD-C3TPB

Size: 20mm 25mm



Small Box Cover (Lids):



No Screws Light Cover

SD-C2LC86-S

Material: Steel

Finish: Black Enamel & Galvanized

Size: 86mm (Dia.)



No Screws Light Cover

SD-C2LC65-S

Material: Steel

Finish: Galvanized Size: 65mm (Dia.)



No Screws Light Cover

SD-C4LC86-S

Material: Steel

Finish: Galvanized Size: 86mm (Dia.)



Cover, Ball & Socket, Earthed

SD-CBSE

Material: Malleable Iron with Copper

Earthwire

Finish: Galvanized
Size: 20mm 25mm



Cover Hook Plate

SD-CCHP-S

Material: Steel

Finish: Galvanized Size: 20mm 25mm



Cover Female Dome

SD-CCFD-S

Material: Steel

Finish: Galvanized
Size: 20mm 25mm



Cover Female Dome

SD-CCFD

Material: Malleable Iron
Finish: Galvanized
Size: 20mm 25mm



Hook & Loop:



Male Loop

SD-CML

Material: Malleable Iron
Finish: Galvanized
Size: 20mm



Male Hook

SD-CMH

Material: Malleable Iron
Finish: Galvanized
Size: 20mm



Female Loop

SD-CFL

Material: Malleable Iron
Finish: Galvanized
Size: 20mm 25mm



Female Hook

SD-CFH

Material: Malleable Iron
Finish: Galvanized
Size: 20mm 25mm

Coupling:



Solid Coupling (Threaded Coupling)

SD-CST

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm

40mm 50mm 3/4" 1" 11/4"

1½" 2"



Earthing Coupling

SD-CEST

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm



Normal Nipple

SD-CNN-S

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm



Long Nipple 30mm

SD-CLN-S

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm



Flanged Coupling

SD-CFST

Material: Malleable Iron

Complete with washer & brass bush

Finish: Galvanized

Size: 20mm 25mm 32mm



Elbow:



Solid Elbow

SD-CSE

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm



Channel Inspection Elbow

SD-CCIE

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm





Internal Thread Normal Bend

SD-CITNB-S

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm

40mm 50mm

³/₄" 1" 1½" 2



Inspection Bend

SD-CIB

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm

Tee:



Solid Tee

SD-CTS

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm



Channel Inspection Tee

SD-CCIT

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm



Bush:



Short Male Bush

SD-CSMB

Material: Brass or Zinc

Finish: Self Colour / Brass Plated Size: 20mm 25mm 32mm

³/₄" 1" 1½" 2"



Long Male Bush

SD-CLMB

Material: Brass or Zinc

Finish: Self Colour / Brass Plated Size: 20mm 25mm 32mm

3/4" 1" 11/2" 2"



Female Bush

SD-CFB

Material: Brass or Zinc

Finish: Self Colour / Brass Plated Size: 20mm 25mm 32mm

1½" 2



Ring:



Extension Ring

SD-CER-S

Material: Steel Finish: Galyanized

Size: 6mm 10mm 13mm

16mm 19mm 25mm 32mm 38mm 50mm

Plug & Gland:



Hexagon Head Plug

SD-CHHP

Material: Malleable Iron Finish: Galvanized

Size: 20mm 25mm 32mm



Slotted Head Plug

SD-CSHP

Material: Brass
Finish: Self Colour
Size: 20mm 25mm



Gland for T.R.S or Similar cable

SD-CGTRS

Material: Brass
Finish: Self Colour
Size: 20mm 25mm





Hexagon Head Reducer

SD-CHHR-S

Material: Steel Finish: Galvanized

Size: 25x20mm 32x20mm 32x25mm,

Locknut:



Light Hexagon Locknut

SD-CI HI N-S

Material: Steel (thickness 3mm)

Finish: Galvanized

Size: 20mm 25mm 32mm



Heavy Hexagon Locknut

SD-CHHI N-S

Material: Steel (thickness 5-6mm)

Finish: Galvanized

Size: 20mm 25mm 32mm



Milled Edge Circular Locknut SD-CCLN-S

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm



Saddle:



Hospital Saddle

SD-CHPS

Material: Malleable Iron Base, Steel Top

Finish: Galvanized

Size: 20mm 25mm



Distance Saddle

SD-CDS

Material: Malleable Iron Base, Steel Top

Finish: Galvanized

Size: 20mm 25mm 32mm

38mm 50mm



Spacer Bar Saddle Clip

SD-SBSC

Material:

Material: Steel

Finish: Galvanized

Size: 20mm 25mm 32mm

40mm 50mm



Finish: Galvanized

Size: 20mm 25mm 32mm

Steel



Clip (Half Saddle)

SD-CHSC-S

Material: Steel

Finish: Galvanized

20mm 25mm 32mm Size:



Steel Crampet

SD-CSC-S

Material: Steel Finish: Galvanized

Size: 20mm 25mm 32mm



Switch & Socket Boxes

Galvanized Gang Box:



1 Gang Switch Box

SD-C1GSBX

Depth: 16mm 25mm

35mm 47mm

Fixing Fittings: 3 fixed & 1 adj. lug

Brass terminal or iron screw 20mm KO's, 25mm KO's 20mm & 25mm KO's or 3

oval KO's



2 Gang Switch Box

SD-C2GSBX

Depth: 16mm 25mm

35mm 47mm

Fixing Fittings: 1 fixed & 1 adj. lug

Brass terminal or iron screw 20mm KO's, 25mm KO's 20mm & 25mm KO's or 4

oval KO's



1+1 Gang Switch Box

SD-C11GSBX

Depth: 35mm Fixing Fittings: 8 fixed lugs

> Brass terminal or iron screw 20mm KO's, 25mm KO's 20mm & 25mm KO's



1+2 Gang Switch Box

SD-C12GSBX

Depth: 35mm Fixing Fittings: 4 fixed lugs

> Brass terminal or iron screw 20mm KO's, 25mm KO's or 20mm & 25mm KO's



1+1+1 Gang Switch Box SD-C111GSBX

Depth: 35mm

Fixing Fittings: 6 fixed lugs

Brass terminal or iron screw 20mm KO's, 25mm KO's or 20mm & 25mm KO's



1+1+2 Gang Switch Box

SD-C112GSBX

Depth: 35mm Fixing Fittings: 6 fixed lugs

> Brass terminal or iron screw 20mm KO's, 25mm KO's or 20mm & 25mm KO's



1 Gang Extension Box

SD-C1GEBX

Depth: 16mm 25mm

Fixing Fittings: 35mm

3 fixed & 1 adj. lugs 20mm KO's, 25mm KO's 20mm & 25mm KO's, or 3

oval KO's



2 Gang Extension Box

SD-C2GEBX

Depth: 16mm 25mm

35mm

Fixing Fittings: 1 fixed & 1 adj. lugs

20mm KO's, 25mm KO's 20mm & 25mm KO's. or

3 oval KO's

Switch & Socket Boxes

Adaptable Box:

SD-CADBX

Adaptable Boxes are manufactured from steel and are available with plain sides or knock-out (20mm).

The standard finish is a Pre-Galvanized.

Where boxes are supplied with knock-outs.

The number and size as follows:

Width of Sides	Size of K.O's	Number of K.O.'s in each side
mm	mm	
3	20	2
4	20	3
6	20	4
9	20	6
12	20	6



Supplied with steel screw as standard M5x8mm. The complete range is manufactured in accordance with BS 4568.

PVC Gang Box:



1 Gang Dry Lining Box SD-C1GDLBX

Depth: 35mm Deep Finish: **PVC** Material Fixing Fittings: 2 adj. tabs



2 Gang Dry Lining Box SD-C2GDLBX

Depth: 35mm Deep Finish: **PVC** Material Fixing Fittings: 2 adj. tabs



Dual Dry Lining Box SD-CDDLBX

Depth: 35mm Deep Finish: **PVC** Material Fixing Fittings: 2 adj. tabs



1 Gang Surface Pattress Box SD-C1GSPBX

Depth: 16, 25, 35 & 47mm Deep

Finish: Urea Material with brass terminal Fixing Fittings:



2 Gang Surface Pattress Box

SD-C2GSPBX

Depth: 25, 35 & 47mm Deep Finish: Urea Material Fixing Fittings: with brass terminal



Support Channel & Accessories


Plain Support Channel:



Plain Support Channel

SD-CPSC1-S

Material: Steel Finish: Galvanized Size: 41x21mm Wall thickness: 1.5-2.5mm Length: 3m/10 ft.




Plain Support Channel

SD-CPSC2-S

Material: Steel Finish: Galvanized Size: 41x41mm Wall thickness: 1.5-2.5mm Length: 3m/10 ft.

Slotted Support Channel:



Slotted Support Channel

SD-CSSC1-S

Material: Steel Finish: Galvanized Size: 41x21mm Wall thickness: 1.5-2.5mm Length: 3m/10 ft.



Slotted Support Channel

SD-CSSC2-S

Material: Steel Finish: Galvanized Size: 41x41mm Wall thickness: 1.5-2.5mm Length: 3m/10 ft.

Channel Nut:



Long Spring Channel Nut

SD-CLSCN-S

Material: Steel Galvanized Finish: Metric Size: M6 M8 M10 M12

with regular spring nut

M14 M16 M18



Short Spring Channel Nut

SD-CSSCN-S

Material: Steel Finish: Galvanized Metric Size: M6 M8 M10 M12 M14 M16 M18

with short spring nut



Channel Nut SD-CPCN-S

Material: Steel

Finish: Galvanized Metric Size: M6 M8 M10 M12

M14 M16 M18

with plain nut



Threaded Rod:



Threaded Rod

SD-TR

Material: Steel Finish: Galvanized

Metric Size: M6 M8 M10 M12 M14

M16 M18 M20 M22

Length: 1M, 1.5M, 2M & 3M



For Support Channels: Plain, Pre Galvanized, Electro Galvanized & Hot Dipped Galvanized are also available upon request

Flexible Steel Conduit:

Flexible metal conduits can be used for cable & wire, protective systems in industrial machines & plants.

Material: Galvanized Steel/Stainless steel 304 & 316

Ip Rating: Ip 40 with fitting type LT-A

Properties: High Flexibility, High Mechanical Strength, Corrosion & Compression Resistance

SD-GFC

Model	Size	Internal Diameter	Outside Diameter
	Inch	mm	mm
SD-GFC-038	3/8	12	16.5
SD-GFC-050	1/2	16	21.0
SD-GFC-075	3/4	20	25.0
SD-GFC-100	1	25	31.0
SD-GFC-125	11/4	32	38.0
SD-GFC-150	1½	38	47.0
SD-GFC-200	2	51	60.0
SD-GFC-250	21/2	64	72.0
SD-GFC-300	3	75	84.0
SD-GFC-400	4	100	112.0
SD-GFC-500	5	125	137.0
SD-GFC-600	6	150	162.0

NOTE: Cut length & other sizes are available upon request.







PVC Coated Flexible Steel Conduit:

PVC Coated Flexible Metal Conduit can be used for cable & wire, protective systems in humid & dusty areas for outdoor applications.

Material: Galvanized Steel, PVC Jacket

Colour: Black, Grey (other on request)

Ip Rating: Ip 67 with fitting type LT-A

Properties: High Flexibility, High Mechanical Strength, Acid & Oil Resistance, Liquid Proof & Full Protection against Corrosion

& Compression Resistance

SD-PFC

Model	Size	Internal Diameter	Outside Diameter
	Inch	mm	mm
SD-PFC-038	3/8	12	16.5
SD-PFC-050	1/2	16	21.0
SD-PFC-075	3/4	20	25.0
SD-PFC-100	1	25	31.0
SD-PFC-125	11/4	32	38.0
SD-PFC-150	1½	38	47.0
SD-PFC-200	2	51	60.0
SD-PFC-250	21/2	64	72.0
SD-PFC-300	3	75	84.0
SD-PFC-400	4	100	112.0
SD-PFC-500	5	125	137.0
SD-PFC-600	6	150	162.0

NOTE: Cut length & other sizes are available upon request.



Flexible Conduit Connector (DPJ Type):

SD-CDPJ

Model	Size Inch
SD-CDPJ-014	1/4
SD-CDPJ-038	3%8
SD-CDPJ-050	1/2
SD-CDPJ-075	3/4
SD-CDPJ-100	1
SD-CDPJ-125	11/4
SD-CDPJ-150	1½
SD-CDPJ-200	2
SD-CDPJ-250	21/2
SD-CDPJ-300	3
SD-CDPJ-400	4
SD-CDPJ-500	5
SD-CDPJ-600	6



Flexible Conduit Connector (DPJ Type)



Flexible Conduit Connector (DPJD Type)

Two Piece Connector for unpacked & PVC Vacuum formed:

SD-CTPC

Material: Brass with Nickel Plated
Thread Size: M16 M20 M25 M32 M40 M50





Flexible Conduit Connector 45°/90° (DNJ/DWJ Type):

SD-CDWJ

Size Inch
3/8
1/2
3/4
1
11/4
1½
2
21/2
3
4
5
6



Flexible Conduit Connector (DWJ Type)



Flexible Conduit Connector (DNJ Type)

One Piece Connector for unpacked Flexible Only (flex to conduit):

SD-COPC

Material: Brass with Nickel Plated
Thread Size: M16 M20 M25 M32 M40 M50









Polyvinyl Carbonate (PVC)

light-weight & easy to install



A range of PVC Conduit fittings and accessories are strong, lightweight, easy to install, cost effective, durable, safe, good insulator and versatile.



PVC Conduits

PVC Rigid Conduit:


SD-PVCCP

Heavy Gauge I.D. x Wall Thickness mm	Medium Gauge I.D. x Wall Thickness mm	Light Gauge I.D. x Wall Thickness mm
20 x 1.8	20 x 1.5	20 x 1.2
25 x 1.9	25 x 1.8	25 x 1.4
32 x 2.5	32 x 2.1	32 x 1.5
38(40) x 2.5	38(40) x 2.2	38(40) x 1.5
50 x 3.2	50 x 2.5	50 x 1.9

NOTE: PVC Rigid Conduit availble in 2.9m & 3.75m length.



PVC Accessories (Black Colour):



PVC Coupling SD-PVCCST

Material: PVC

Size: 20mm 25mm 32mm

38(40)mm 50mm



PVC Female Adaptor SD-PVCFA

D-PVCFA

Material: PVC

Size: 20mm 25mm 32mm

38(40)mm 50mm



PVC Normal Bends

SD-PVCNB

Material: PVC

Size: 20mm 25mm



PVC Space Bar Saddle Clip

SD-PVCSBSC


Material: PVC

Size: 20mm 25mm 32mm

38(40)mm 50mm

PVC Conduits


PVC Junction Box:



1 Way SD-PVC1JB

Material: PVC

Size: 20mm 25mm




2 Way (through)

SD-PVC2TJB

Material: PVC


Size: 20mm 25mm



A Way (angle) SD-PVC2AJB

Material: PVC


Size: 20mm 25mm



3 Way SD-PVC3TJB

Material: PVC

Size: 20mm 25mm



4 Way SD-PVC4WJB

Material: PVC

Size: 20mm 25mm

PVC Adaptable Box:

SD-PVCADBX

Material: PVC

Size: 75 x 75 x 50mm

100 x 100 x 75mm (110x110x78) 150 x 100 x 75mm (165x125x100) 150 x 150 x 75mm (235x180x100) 225 x 225 x 75mm (320x250x130)





PVC Switch/Socket Cover:



PVC SWT / SKT Cover


SD-PVCSWCV

Material:

PVC

Size:

87mm x 87mm



PVC Circular Lid

SD-PVCCLD

Material: PVC

Size: 65mm 85mm



PVC SWT / SKT Box

SD-PVCSWBX

Material:

Size: 87mm x 87mm

PVC



PVC Loop-In Box

SD-PVCLIBX

Material: PVC Size: 20mm





For further information on any aspect of the Shield range of Conduit System please contact your nearest office.

UNITED KINGDOM

Unit 3, Endeavour Drive, Basildon-Essex, SS14 3WF, United Kingdom. Email: info@shieldglobal.com

> Tel: +44 1708 377731 Fax: +44 1708 347637

MIDDLE EAST & AFRICA

Jebel Ali Free Zone, Dubai, UAE Email: shieldme@shieldglobal.com

Tel: +971 4 881 2070 Fax: +971 4 881 2198

