












ROCKWOOL SANDWICH PANEL

S.No.	Accessories	Usage	Description
1	Self drilling screws 6.3 x 25	Length of screw is based on the Panel thickness, ranging from 40 mm to 240 mm	
2	Self drilling countersunk head screw	Length of screw is based on the Panel thickness, ranging from 40 mm to 240 mm	
3	Self drilling screws 6 / 5.5 x 130 (Recommended washer \varnothing 16 mm)	Length of screw is based on the Panel thickness, ranging from 40 mm to 240 mm	
4	Self drilling screws 6 / 5.5 x 130 (E19)	Length of screw is based on the Panel thickness, ranging from 40 mm to 240 mm	
5	Self tapping screws 6.5 x 76		
6	Self tapping screws 4.8 x 16		
7	Self tapping screws 6.3 x 25	Used in the rounded corner connection	

8	Self tapping screws 6.5 x 25	Used in the Gable detail	
9	Anchor screw		
10	Screw for Concrete 7.5x42 VBK ZN		
11	Screw for Concrete BS-R 6.3x35 E19		
12	Screw for plate 6.3x25A2 EX BR RS19		
13	Blind Rivet 4 x 10 A2	Fastening flashing to the wall panel. Body: Stainless steel 304, Cu Nail: Stainless Steel 304	
14	Blind Rivet 4 x 8	For fixing the panel drip profile with the panel @ horizontal installation.	

15	Blind Rivet 5.2 x 20.5 AL		
16	Blind Rivet 5.2 x 19.1	For fixing the loose Rockwool with the Panel support profile @ Horizontal installation. Grip range: 1.5 - 6.4 mm	
17	False rivet 4 x 10	Over the cover flashing through the panel. Grip range: 12 - 15.9 mm	
18	Bulb tite rivet		
19	Anchor bolts		
20	SPIKE anchor 4.8x32		
21	Washer EPDM 3x3/28		

22	Washer for all the screws		Based on the type of screw
23	Saddle washer	Roof system, Washer dia 28 mm with dia 3 mm hole	
24	screw caps	Used wherever the screws are exposed as per the Ral color used in the Panel	