

KNOCK OUT

VENTILATION

PARTITION -

KNOCK OUT

800

FIRE HOSE REEL

FIRE EXTINGUISHER **

BREAK GLASS

4

SAFETY SEAL

2

SAFETY SEAL

WITH KEY

BREAK GLASS

 \Longrightarrow \circ \Longleftrightarrow

30TYP

NAFFCO

1650

NOTES:-

1. ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE SPECIFIED

BILL OF MATERIALS				
ITEM NO.	DESCRIPTION	MATERIAL	QTY.	
1.	CABINET BODY	1.2mm ELECTRO GALVANISED STEEL SHEET	1	
2.	SOLID DOOR	1.2mm ELECTRO GALVANISED STEEL SHEET	2	
3.	BUSH PIN HINGES	MILD STEEL	4	
4.	SPRING LOCK WITH KEY	ALLOY STEEL	2	

SPECIFICATIONS			
MODEL	NF SMK 900		
PAINT FINISH	AS PER REQUIREMENT		
DOOR OPENING	RIGHT OR LEFT		
CABINET TO ACCOMMODATE			
TOP COMPARTMENT	1"x30Mtr. OR 3/4"x30Mtr. CABINET MOUNTED / WALL MOUNTED FIRE HOSE REEL		
BOTTOM COMPARTMENT	5Kg. CO2 EXTINGUISHER, 6Kg. DCP EXTINGUISHER 2.5" LANDING VALVE OR 1.5"x 30Mtr HOSE RACK / 2.5"x30Mtr. HOSE RACK		
BRACKET POSITION	RIGHT OR LEFT		
VENTILATION	BOTH SIDE OF CABINET		
KNOCK OUT	AS PER INLET LINE		
GENERAL TOLERANCE	±5MM		
UNIT HEIGHT	1650MM		
UNIT WIDTH	800MM		
UNIT DEPTH	300MM		
**LOWER COMPARTMENT PRINTING WILL CHANGE ACCORDING TO THE EQUIPMENTS TO BE ACCOMMODATED			