

## ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE SPECIFIED

| BILL OF MATERIALS   |  |      |
|---------------------|--|------|
| SCRIPTION           | MATERIAL                               | QTY. |
| BODY                | 1.2mm STAINLESS STEEL<br>MIRROR FINISH | 1    |
| OOR (WIRED / CLEAR) | 1.2mm STAINLESS STEEL<br>MIRROR FINISH | 2    |
| BES                 | STAINLESS STEEL                        | 3    |
| LOCK WITH KEY       | ALLOY STEEL                            | 2    |

| SPECIFICATIONS                                  |  |  |
|---|--|--|
|   | NF SSMGK 900   |  |
|   | STAINLESS STEEL<br>MIRROR FINISH   |  |
| G   | RIGHT OR LEFT  |  |
| CABINET TO ACCOMMODATE                          |  |  |
| RTMENT  | 1"x30Mtr. OR 3/4"x30Mtr.<br>CABINET MOUNTED /<br>WALL MOUNTED<br>FIRE HOSE REEL  |  |
| MPARTMENT                                       | 5Kg. CO2 EXTINGUISHER,<br>6Kg. DCP EXTINGUISHER<br>2.5" LANDING VALVE OR<br>1.5"x 30Mtr HOSE RACK /<br>2.5"x30Mtr. HOSE RACK |  |
| OSITION   | RIGHT OR LEFT  |  |
|   | AS PER INLET LINE  |  |
| OLERANCE  | ±5MM   |  |
|   | 1650MM   |  |
|   | 800MM  |  |
|   | 310MM  |  |
| IPARTMENT PRINTING WILL CHANGE ACCORDING TO THE |  |  |
|   |  |  |