

CLEAN AGENT FIRE EXTINGUISHERS



PRODUCT DESCRIPTION

NAFFCO UL Listed Clean Agent fire extinguishers (HALOTRON) is a clean, non-conductive gaseous agent that is an excellent replacement for Halon 1211 extinguishers. Clean Agent is suitable for use on Class A, Class B, and Class C fires.



FEATURES

- Residue-free Hydro-chlorofluorocarbon gas agent pressurized with argon.
- Typically used for protecting sensitive electronic equipment in offices, classrooms, churches, parking garages and hotel/motel assembly halls and guest areas.
- Also used for protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.
- Not suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.
- Clean Agent Extinguishers are USCG Approved (Marine Application)

SPECIFICATION

Model Number	N 05L FSA*/ N 05L FSB**	N 05L HSA***	N 11L SA*/ N 11L SB**	N 15L SA*/ N 15L SB**
Agent Capacity	5 lb. (2.27 kg)	5.5 lb. (2.49 kg)	11 lb. (5 kg)	15.5 lb. (7.03 kg)
UL Rating	5-B:C	5-B:C	1-A:10-B:C	2-A:10-B:C
Discharge Time	9 sec.	9 sec.	9 sec.	13 sec.
Range (FT/M)	9-15/2.7-4.5	9-15/2.7-4.5	9-15/2.7-4.5	12-18/3.7-5.5
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	125 psi (862 kPa)
Operating Temperature Range	-40°F to +120° F	-40°F to +120° F	-40°F to +120° F	-40°F to +120° F
Bracket	Wall	Wall	Wall	Wall
USCG Approval (Marine Application)	Type B:C size I	Type B:C size I	Type B:C size I	Type B:C size II
Ship Weight	9.25 lb. (4.2 kg)	10.0 lb. (4.5 kg)	21.25 lb. (9.6 kg)	25.75 lb. (11.75 kg)
Unit Height	16.375 in (41.6 cm)	16.375 in (41.6 cm)	17.5 in (44.5 cm)	17.5 in (44.5 cm)
Unit Width	6.5 in (16.5 cm)	6.5 in (16.5 cm)	8.625 in (21.9 cm)	8.625 in (21.9 cm)
Unit Diameter	4.25 in (10.8 cm)	4.25 in (10.8 cm)	7 in (17.8 cm)	7 in (17.8 cm)

* Aluminum Head valve

** Brass Head valve

*** Aluminum head valve with discharge hose