

ABC & E DRY POWDER PORTABLE FIRE EXTINGUISHERS (AS/NZS 1841.5)



FEATURES


- Mono ammonium phosphate based dry chemical agent. Capable of fighting Class A, B, C and E fires.
- Australian & New Zealand Standard AS/NZS 1841.5, certified by Global-Mark Pty Ltd.
- High quality polyester paint.
- Controlled discharge.
- Brass nickel plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique colour coded handle and base (optional).
- Rechargeable and easy to service.



Ideal Use: Houses, office, buildings, warehouses, farms, wood working area etc.
**Note:* Not recommended for use on expensive and delicate equipment like computers, etc.

SPECIFICATION

Model Number	1NP-A	2.1NP-A	2.5 NP-A	3NP-A	4.5NP-A	4.5NP-AS	9 NP-A	9 NP-AS
Extinguisher Capacity	1 Kg	2.1 Kg	2.5 KG	3 Kg	4.5 Kg	4.5 Kg	9 KG	9 KG
Propellant	95% Nitrogen + 5% Helium							
Fire Rating	1A:20B:C:E	2A:20B:C:E	3A:40B:C:E	3A:40B:C:E	4A:60B:C:E	4A:60B:C:E	6A:60B:C:E	6A:60B:C:E
Working Pressure	10 Bar	13.5 Bar	13.5 Bar	13.5 Bar	13.5 Bar	13.5 Bar	13.5 Bar	13.5 Bar
Maximum Operating Pressure	18.5 Bar @ 60°C							
Test Pressure	30 Bar							
Total Weight	2.5 Kg	4.3 kg	4.3 kg	5.95 Kg	8.15 Kg	8 Kg	14.5 KG	14.2 KG
Range of Discharge	4 - 5 Mtr.	5 - 7 Mtr.	5 - 7 Mtr.	6 - 7 Mtr.	7 - 8 Mtr.	7 - 8 Mtr.	6 – 8 Mtr	6 – 8 Mtr
Duration of Discharge	8 Sec.	11 - 14 Sec.	18 - 22 Sec.	13 -14 Sec.	16 - 18 Sec.	16 - 18 Sec.	22 - 24 Sec	22 - 24 Sec
Hose Length with Nozzle	N/A	365 mm	435 mm	435 mm	465 mm	465 mm	550 mm	550 mm
Operating Temperature	-20°C to +60°C							
Cylinder Material	CRCA Steel Sheet					Steel Sheet	CRCA Steel Sheet	Steel Sheet
Height x Diameter (mm)	337 x 78	385 x 110	421 x 120	420 x 132	520 x 150	515 x 150	625 X 185	625 X 185



1. Valve / Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. Discharge Hose
6. Syphon Tube
7. Hose Holder
8. Discharge Nozzle
9. PVC Base

