

# BC DRY POWDER PORTABLE FIRE EXTINGUISHERS



2797



0086/2021



## FEATURES


- Potassium Bicarbonate (PBC) based dry chemical agent. Capable of fighting Class B and C
- Kitemark approved Potassium Bicarbonate (PBC) to BSEN3.
- Cylinders compliance to council directive 2014/68/EU (PED) is certified by BSI (2797).
- Certified by BSI under marine equipment directive, 2014/90/EU (MED)
- High quality polyester paint.
- Controlled discharge.
- Brass nickel plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color coded handle and base (optional).
- Rechargeable and easy to service.
- Choice of capacity from 4 to 12 kg.

**\*IDEAL USE:** Houses, office, buildings, warehouses, farms, wood working area etc.

**\*NOTE:** Not recommended for use on expensive and delicate equipment like computers, etc.

## SPECIFICATION

Model Number	NPS4	NPS6	NPS9	NPS12
Extinguisher Capacity	4 kg.	6 kg.	9 kg.	12 kg.
Propellant	95% Nitrogen + 5% Helium			
Fire Rating	113B	183B	233B	233B
Working Pressure	15 bar	15 bar	15 bar	15 bar
Maximum Operating Pressure	18.5 bar @ 60°C			
Test Pressure	30 bar			
Total Weight	7.5 kg.	10 kg.	14 kg.	17.8 kg.
Range of Discharge	7-8 m	6-8 m	6-8 m	6-8 m
Duration of Discharge	13-15 sec.	18-20 sec.	22-24 sec.	28-30 sec.
Hose Length with Nozzle	457 mm	534 mm	534 mm	617 mm
Operating Temperature	-20°C to +60°C			
Cylinder Material	CRCA Sheet			
Height x Diameter (mm)	408 x 150	520 x 150	534 x 185	620 x 185



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. Discharge Hose
6. Syphon Tube
7. Hose Holder
8. Discharge Nozzle
9. PVC Base

