


**2 LTR. ECO BARID FOAM FIRE EXTINGUISHER -
MODEL: NF 2EB**



NOTES :-

1. ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE SPECIFIED

BILL OF MATERIAL

ITEM No.	DESCRIPTION	MATERIAL	QTY.
1	CYLINDER	CRCA STEEL SHEET	1
2	BRACKET	PVC	1
3	NOZZLE	PVC	1
4	EXTINGUISHER VALVE	BRASS CHROME PLATED	1
5	PRESSURE GAUGE	BRASS CHROME PLATED	1
6	DIP TUBE	PVC	1

SPECIFICATION:-

MODEL	NF 2EB
EXTINGUISHER CAPACITY	2 Ltr.
PROPELLENT	95% NITROGEN + 5% HELIUM
FIRE RATING	80A 89B 5F
WORKING PRESSURE	14 BAR
MAX. OP. PRESSURE	18.5 BAR @ 60°C
TEST PRESSURE	30 BAR
TOTAL WEIGHT	4.71KG
RANGE OF DISCHARGE	1-2 Mtr.
DURATION OF DISCHARGE	8-10 Sec.
WORKING TEMPERATURE	+5°C TO +60°C
CYLINDER MATERIAL	CRCA STEEL SHEET