

# ECO BARID FOAM FIRE EXTINGUISHER



## PRODUCT DESCRIPTION

NAFFCO stored pressure type Eco barid foam extinguisher are multipurpose, ideal for fires involving volatile liquids and freely burning material such as paper, cloth, wood, furniture and cooking oil or fat fires.




## FEATURES

- LPCB certified to BS EN 3
- Eco barid foam agent is capable of fighting class A, B & F fires
- Thermoplastic internal coating to prevent corrosion
- High quality external polyester powder coating
- Brass nickel chrome plated head value with squeeze operation
- Controlled discharged

## FOAM FIRE EXTINGUISHER - STORED PRESSURE

Model Number	NF 2EB	NF 3EB	NF 6EB	NF 9EB
Cylinder Capacity	2 Liter	3 Liter	6 Liter	9 Liter
Propellant	95% Nitrogen + 5% Helium			
Fire Rating	8A 89B 5F	8A 113B 25F	21A 183B 40F	27A 183B 40F
Working Pressure	14 bar	14 bar	14 bar	14 bar
Maximum Operating Pressure	18.5 bar @ 60°C			
Test Pressure	30 bar	30 bar	30 bar	30 bar
Total Weight (excluding Hose Assembly)	4.71 kg.	6.36 kg.	11.5 kg.	16.5 kg.
Discharge Range	1-2 m	1-2 m	6 m	7 - 8 m
Discharge Time	8 - 10 sec.	12 - 15 sec.	22 - 25 sec.	30 - 34 sec.
Total Weight (excluding Hose Assembly)	4.71 kg.	6.36 kg.	11.5 kg.	16.5 kg.
Hose length with nozzle	n/a	n/a	680 mm	680 mm
Working Temperature	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
Cylinder Material	Cold Rolled Steel Sheet			
Outside Diameter	110±2 mm	134±2 mm	150±2 mm	185±2 mm
Overall Height of the Extinguisher	±5.0 420 mm	±5.0 425 mm	±5.0 625 mm	±5.0 625 mm



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. PVC Internal Coating
6. Discharge Hose
7. Syphon Tube
8. Hose Holder
9. Filter
10. Discharge Nozzle
11. PVC Base

