

FOAM PORTABLE FIRE EXTINGUISHERS (AS/NZS 1841.4)



FEATURES

- AFFF (6%) Synthetic Aqueous Film - Forming Foam Agent capable of fighting Class A, B fires.
- Australian & New Zealand Standard AS/NZS 1841.4, certified by Global-Mark Pty Ltd.
- High quality external polyester paint.
- Thermoplastic internal coating to prevent corrosion.
- Spray nozzle to provide high fire rating.
- Controlled discharge.
- Brass nickel chrome plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color code handle and base (Optional).
- Rechargeable and easy to service.




Ideal Use: Schools, Theaters, Apartments, Offices and Dry Goods Store.

**Note:* Water based Extinguishers are not suitable for life involving electrical risk.

SPECIFICATION

Model Number	6-NF-A	9-NF-A	9 NFS-A
Extinguisher Capacity	6 Ltr	9 Ltr	9 Ltr
Propellant	95% Nitrogen + 5% Helium		
Fire Rating	3A 10B	3A 20B	3A 20B
Working Pressure	13.5 Bar		
Maximum Operating Pressure	18.5 Bar @ 60°C		
Test Pressure	30 Bar		
Total Weight	11.5kg	16.5 Kg	12.8 Kg
Range of Discharge	6 Mtr.	7 - 8 Mtr.	6 - 7 Mtr.
Duration of Discharge	18 Sec.	40 Sec.	40 - 45 Sec.
Hose Length with Nozzle	680mm		760mm
Operating Temperature	+5°C to +60°C		
Cylinder Material	CRCA Steel Sheet		Stainless Steel
Height x Diameter (mm)	610 x 150		638 x 180



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. PVC Internal Coating
6. Discharge Hose
7. Syphon Tube
8. Hose Holder
9. Filter
10. Discharge Nozzle
11. PVC Base

