


**6 LTR. FOAM FIRE EXTINGUISHER -
MODEL: NFI 6**



NOTES :-

1. ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE SPECIFIED

BILL OF MATERIAL

ITEM No.	DESCRIPTION	MATERIAL	QTY.
1	CYLINDER	CRCA STEEL SHEET	1
2	BRACKET HOLDER	CRCA STEEL SHEET	
3	HOSE	RUBBER	1
4	EXTINGUISHER VALVE	BRASS CHROME PLATED	1
5	PRESSURE GAUGE	BRASS CHROME PLATED	1
6	DIP TUBE	PVC	1
7	NOZZLE	PVC	1
8	BASE	PVC	1
9	HOSE GRIP	RUBBER	1
10	FILTER	PVC	1

SPECIFICATION:-

MODEL	NFI 6
EXTINGUISHER CAPACITY	6 Ltr.
PROPELLENT	95% NITROGEN + 5% HELIUM
FIRE RATING	21A 144B
WORKING PRESSURE	14 BAR
MAX. OP. PRESSURE	18.5 BAR @ 60°C
TEST PRESSURE	30 BAR
TOTAL WEIGHT	11.5KG
RANGE OF DISCHARGE	6-7Mtr.
DURATION OF DISCHARGE	22-28 Sec.
OPERATING TEMPERATURE	+5°C TO +60°C
CYLINDER MATERIAL	CRCA STEEL SHEET