

# FOAM PORTABLE FIRE EXTINGUISHERS

## PRODUCT DESCRIPTION

NAFFCO stored pressure and cartridge operated foam extinguishers are multipurpose, ideal for fires involving volatile liquids and freely burning materials such as paper, cloth, wood and furniture. Suitable for Class A and Class B fire risks.



## FEATURES

- AFFF (6%) Synthetic Aqueous Film - Forming Foam Agent capable of fighting Class A, B fires.
- Kitemark/LPCB certified to BS EN3.
- Cylinders compliance to council directive 2014/68 EU (PED) is certified by BSI (2797).
- Certified by BSI under marine equipment directive, 2014/90/EU (MED)
- High quality external polyester paint.
- Thermoplastic internal coating to prevent corrosion.
- Spray nozzle to provide high fire rating.
- Controlled discharge.
- Brass nickel chrome plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color code handle and base (Optional).
- Rechargeable and easy to service.


**\*IDEAL USE:** Schools, Theatres, Apartments, Offices and Dry Goods Store.

**\*NOTE:** Water based Extinguishers are not suitable for life involving electrical risk.

## FOAM FIRE EXTINGUISHER - STORED PRESSURE/EXTERNAL CARTRIDGE TYPE

Model Number	NF 3*	NF 3X*	NF 6	NFI 6	NF 6X	NF 9	NFI 9	NFA 9*	NF 9X*	NFC 6X*	NFC 9X*
Extinguisher Capacity	3 L	3 L	6 L	6 L	6 L	9 L	9 L	9 L	9 L	6 L	9 L
Propellant	95% Nitrogen + 5% Helium									CO <sub>2</sub>	
Fire Rating	8A 70B	8A 70B	21A 144B	21A 144B	27A 144B	21A 183B	21A 183B	21A 183B	27A 233B	27A 144B	34A 233B
Working Pressure	14 bar										
Maximum Operating Pressure	18.5 bar @ 60°C										
Test Pressure	30 bar										
Total Weight	11.5 kg	11.5 kg	11.5 kg	11.5 kg	15.5 kg	15.5 kg	15.5 kg	14.5 kg	15.5 kg	12.5 kg	17 kg
Range of Discharge	6 m	6 m	6 m	6-7 m	6-7 m	7-8 m	7-8 m	7-8 m	7-8 m	6 m	7-8 m
Duration of Discharge	22-25 sec.	25-27 sec.	22-25 sec.	22-28 sec.	30-32 sec.	32-35 sec.	32-35 sec.	32-35 sec.	35-38 sec.	18-20 sec.	35-40 sec.
Hose Length with Nozzle	N/A	N/A	680 mm	680 mm	680 mm	680 mm	680 mm	680 mm	610 mm	680 mm	680 mm
Operating Temperature	+5°C to +60°C										
Cylinder Material	CRCA Steel Sheet										
Height x Diameter (mm)	420 x 132	420 x 132	610 x 150	610 x 150	610 x 150	630 x 185	630 x 185	630 x 185	630 x 185	630 x 185	630 x 185

\*LPCB Approval only, External Cartridge Operated.



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. PVC Internal Coating
6. Discharge Hose
7. Syphon Tube
8. Hose Holder
9. Filter
10. Discharge Nozzle
11. PVC Base

