

WATER PORTABLE FIRE EXTINGUISHERS (AS/NZS 1841.2)



FEATURES


- Water, a liquid agent only recommended for fighting Class A Fire.
- Australian & New Zealand Standard AS/NZS 1841.2, certified by Global-Mark Pty Ltd.
- High quality external polyester paint.
- Thermoplastic internal coating to prevent corrosion.
- Spray nozzle to provide high fire rating.
- Controlled discharge.
- Brass nickel chrome plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color code handle and base (Optional).
- Rechargeable and easy to service.



Ideal Use: Schools, Theatres, Apartments, Offices and Dry Goods Store.
**Note:* Water based Extinguishers are not suitable for life involving electrical risk.

SPECIFICATION

Model Number	9-NW-A	9NWS-A
Extinguisher Capacity	9 Ltr	
Propellant	95% Nitrogen + 5% Helium	
Fire Rating	3A	3A
Working Pressure	13.5 Bar	
Maximum Operating Pressure	18.5 Bar @ 60°C	
Test Pressure	30 Bar	
Total Weight	15.5kg	12.7kg
Range of Discharge	6 -7 Mtr.	
Duration of Discharge	43 Sec.	45 - 50 Sec.
Hose Length with Nozzle	680mm	605mm
Operating Temperature	+5°C to +60°C	
Cylinder Material	CRCA Steel Sheet	Stainless Steel
Height x Diameter (mm)	630 x 185	638 x 180



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. PVC Internal Coating
6. Discharge Hose
7. Syphon Tube
8. Hose Holder
9. Filter
10. Discharge Nozzle
11. PVC Base

