

WATER PORTABLE FIRE EXTINGUISHERS

PRODUCT DESCRIPTION

NAFFCO stored pressure and cartridge operated water extinguishers are characterised by their high performance, and simple method of operation ideal for tackling freely burning materials such as paper, cloth, wood and furniture. These are good general purpose fire extinguishers and widely used for their cost effectiveness.



CERTIFICATE NO:463
(Ref redbooklive.com)



FEATURES

- Water, a liquid agent only recommended for fighting Class A Fire.
- Kitemark/LPCB certified to BS EN3.
- Cylinders compliance to council directive 2014/68/EU (PED) is certified by BSI (2797).
- Certified by BSI under marine equipment directive, 2014/90/EU (MED)
- High quality external polyester paint.
- Thermoplastic internal coating to prevent corrosion.
- Spray nozzle to provide high fire rating.
- Controlled discharge.
- Brass nickel chrome plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color code handle and base (Optional).
- Rechargeable and easy to service.


***IDEAL USE:** Schools, Theatres, Apartments, Offices and Dry Goods Store.

***NOTE:** Water based Extinguishers are not suitable for life involving electrical risk.

WATER FIRE EXTINGUISHER - STORED PRESSURE/EXTERNAL CARTRIDGE TYPE

Model Number	NW 6	NW 6X*	NWNI6	NW N6	NW 9	NW N9	NWNI 9	NWA 9*	NW 9X	NWC 6X*	NWC 9X*
Extinguisher Capacity	6 L	6 L	6 L	6 L	9 L	9 L	9 L	9 L	9 L	6 L	9 L
Propellant	95% Nitrogen + 5% Helium									CO ₂	
Fire Rating	13A	13A	13A	13A	21A	13A	13A	21A	21A	13A	21A
Working Pressure	14 bar										
Maximum Operating Pressure	18.5 bar @ 60°C										
Test Pressure	30 bar										
Total Weight	11.5 kg	11.5 kg	11.5 kg	11.5 kg	15.5 kg	15.5 kg	15.5 kg	14.5 kg	15.5 kg	12.5 kg	17 kg
Range of Discharge	6 m	6 m	6 m	6-7 m	6-7 m	7-8 m	7-8 m	7-8 m	7-8 m	6 m	7-8 m
Duration of Discharge	22-25 sec.	25-27 sec.	22-25 sec.	22-28 sec.	30-32 sec.	32-35 sec.	32-35 sec.	32-35 sec.	35-38 sec.	18-20 sec.	35-40 sec.
Hose Length with Nozzle	680 mm										
Operating Temperature	+5°C to +60°C										
Cylinder Material	CRCA Steel Sheet										
Height x Diameter (mm)	625 x 150	625 x 150	625 x 150	625 x 150	630 x 185	630 x 185	630 x 185	630 x 185	630 x 185	630 x 185	630 x 185

*LPCB Approval only, External Cartridge Operated.



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. PVC Internal Coating
6. Discharge Hose
7. Syphon Tube
8. Hose Holder
9. Filter
10. Discharge Nozzle
11. PVC Base

