

FIRE HOSE REEL - MANUAL, FIXED TYPE
 MODEL: 19 NFH - 040M/SS



NOTES :-

1. ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE SPECIFIED
2. HOSE REEL ASSEMBLY COMPLIANCE TO CPR DIRECTIVE 305/2011/EU IS CERTIFIED BY BSI (0086)..
3. THE NOZZLE HAVE SHUT, JET AND SPRAY CONTROL SETTINGS
4. THE MINIMUM FLOW RATE OF HOSE REELS IN JET AND SPRAY SETTING IS 41 LPM AT 6 BAR PRESSURE

BILL OF MATERIALS

| ITEM NO. | DESCRIPTION | MATERIAL | QTY. |
|----------|---------------------|---------------------------|------|
| 1. | HOSE 3/4"x30 M LG. | PVC COMPOUND | 1 |
| 2. | WATER BRANCH - 3/4" | PA, RED INJECTION MODULED | 1 |
| 3. | HOSE HANDLE | HDPE, BLACK | 1 |
| 4. | HOSE CLAMP | STAINLESS STEEL | 3 |
| A | HOSE REEL ASSY. | ----- | 1 |

SPECIFICATIONS:-

WORKING, TEST AND MINIMUM BURST PRESSURE OF HOSE REEL

| NOMINAL DIA. OF HOSE MM | WORKING PRESSURE (MPA) | TEST PRESSURE (MPA) | MIN. BURST PRESSURE (MPA) |
|-------------------------|------------------------|---------------------|---------------------------|
| 19 | 1.2 | 1.8 | 3.0 |

MANUFACTURING STANDARD : EN 671-1 : 2012

