

Kitemark™ Certificate

This is to certify that:

National Fire Fighting
Manufacturing Co Ltd
Plot No. S10201
Jebel Ali Free Zone South
P O Box 17014
Dubai
United Arab Emirates

Holds Certificate Number:

KM 621573

In respect of:

BS EN 14384
Pillar Fire Hydrants

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:

Shahm Barhom, Group Product Certification Director

First Issued: 2015-06-25

Latest Issue: 2023-05-03

Effective Date: 2023-05-03

Expiry Date: 2025-01-23

Page: 1 of 4



Kitemark™ Certificate

No. KM 621573

Description	Model No.	Additional Information	Branded As
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NHC-800	Hand wheel operation, Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NHC-1200	Hand wheel operation, Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" Gate valve with BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFHV-800	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" Gate valve with BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFHV-1200	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" Gate valve with BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHV-800	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" Gate valve with BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHV-1200	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFBQ-800	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFBQ-1200	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFBQ-800	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFBQ-1200	Complete Ductile iron body construction, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFBQC-800	Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO

First Issued: 2015-06-25

Latest Issue: 2023-05-03

Effective Date: 2023-05-03

Expiry Date: 2025-01-23

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 621573

Description	Model No.	Additional Information	Branded As
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFHQC-1200	Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHQC-800	Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHQC-1200	Complete Ductile iron body construction with Aluminium / GRP protection cover, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFHQS-CD800	Complete Ductile iron body construction with Single body casting of Upper Barrel, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	100 NFHQS-CD1200	Complete Ductile iron body construction with Single body casting of Upper Barrel, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHQS-CD800	Complete Ductile iron body construction with Single body casting of Upper Barrel, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling and 4" BSRT Pumper outlet.	150 NFHQS-CD1200	Complete Ductile iron body construction with Single body casting of Upper Barrel, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling, 1 x 4" BSRT pumper connection and 1 x 4" Flanged outlet.	150 NFHQM-800	Complete Ductile iron body construction with 4" flanged outlet for Monitor connection, PN 16 Pressure rating.	NAFFCO
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" BS 336 Coupling, 1 x 4" BSRT Pumper connection and 1 x 4" Flanged outlet.	150 NFHQM-1200	Complete Ductile iron body construction with 4" flanged outlet for Monitor connection, PN 16 Pressure rating.	NAFFCO
4" (DN 100) Dry pillar hydrant inlet with 2 x 2½" female instantaneous BS 336 outlets with cap & chain and one 4" male/female BS 336 BSRT outlet with cap & chain	100 NFHQV-CDX	Complete Ductile iron body construction with single casting of upper barrel. PN 16 Pressure rating	NAFFCO

First Issued: 2015-06-25

Latest Issue: 2023-05-03

Effective Date: 2023-05-03

Expiry Date: 2025-01-23

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 621573

Description	Model No.	Additional Information	Branded As
6" (DN 150) Dry pillar hydrant inlet with 2 x 2½" female instantaneous BS 336 outlets with cap & chain and one 4" male/female BS 336 BSRT outlet with cap & chain	150 NFHQV-CDX	Complete Ductile iron body construction with single casting of upper barrel. PN 16 Pressure rating	NAFFCO

The above pillar fire hydrants are certified to BS EN 14384:2005.



First Issued: 2015-06-25
Latest Issue: 2023-05-03

Effective Date: 2023-05-03
Expiry Date: 2025-01-23

Page: 4 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.