

HBOR.EX15350 - Hydrants

Hydrants

NATIONAL FIRE FIGHTING MFG FZ CO
 PO BOX 17014
 JEBEL ALI FREE ZONE
 DUBAI, United Arab Emirates

EX15350

Base-valve design:

Model	Base-valve Size, in.	Hose Outlet (No. of Outlets), in.	Pumper Outlet (No. of Outlets), in.	Rated Pressure, psig
150-NFH(M)	5-1/4	(2) 2-1/2	(1) 4-1/2	250
150-NFH(F)	5-1/4	(2) 2-1/2	(1) 4-1/2	250

Model 150-NFH(M) with a mechanical joint (MJ) connection to fire main.

Model 150-NFH(F) with ASME B16.5 Class 150 flanged connection to fire main.

Wet-barrel design:

Model	House Outlet (No. of Outlets) in.	Pumper Outlet (No. of Outlets) in.	Rated Pressure, psig
150NF-WH	(2) 2-1/2	(1) 4 or 4-1/2 threaded	250
150NF-WHM+	(2) 2-1/2	(1) 4 or 4-1/2 threaded	250

+ Model 150NF-WHM hydrant incorporates a 3 or 4 in. size monitor flange on the top of the hydrant.

Last Updated on 2023-04-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."