

DOUBLE JACKET FIRE HOSE



A) UL LISTED HOSE

FEATURES


- This durable, double jacket hose is constructed of 100% high tensile strength polyester yarns, both wrap and filler, and lined with a high-tech EPDM tube. Its engineered design guarantees minimum weight with maximum durability and flexibility. The UL Listed Double Jacket Fire Hose and its assemblies under these specifications shall be constructed with superior quality materials, manufactured in accordance with National Fire Protection Association (NFPA) 1961 standard.
- Outstanding abrasion resistance.
- Tough, dependable and lightweight attach hose.
- A stripe of a contrasting color running the full length of the hose can be provided into the jacket to meet NFPA recommendations for pump panel.

HOSE DATA

- Available colors: White & Red

STANDARD LENGTH

- 30 meters, Other lengths available upon request.



SPECIFICATION

| Model Number | Diameter (in.) | Service Test Pressure (bar/psi) | Hydrostatic Strength Test Pressure (bar/psi) | Standard Compliance/ Approvals |
|--------------|----------------|---------------------------------|--|--------------------------------|
| NF-FH38DJ | 1.5 | 21/300 | 63/900 | UL19, NFPA 1961/UL Listed |
| NF-FH65DJ | 2.5 | 21/300 | 63/900 | |
| NF-FH38DJ-HP | 1.5 | 28/400 | 83/1200 | |
| NF-FH45DJ-HP | 1.75 | 28/400 | 83/1200 | |
| NF-FH52DJ-HP | 2 | 28/400 | 83/1200 | |
| NF-FH65DJ-HP | 2.5 | 28/400 | 83/1200 | |
| NF-FH75DJ-HP | 3 | 28/400 | 83/1200 | |