

B) KITEMARK AND LPCB APPROVED HOSE, TYPE 2

Single jacket fire hose consists of an impermeable elastomeric lining, a synthetic fibre reinforcement and externally applied elastomeric coating to the reinforcement. Delivery hoses are non-percolating lay flat type used in fire fighting purposes. Hoses are suitable for use with couplings with the requirements of BS 336: 2010 standards. Hose is intended for use at working pressure not exceeding 15 bar. Delivery hose are manufactured to comply BS 6391: 2009 Standards.



FEATURES

- BSI Kitemark and LPCB Certified.
- Light weight and flexible.
- Hose belongs to Type 2 with Elastomeric lining, Synthetic fibre reinforcement and elastomeric coating on the reinforcement.
- Hose provides good protection against the absorption of liquids and resistance of the reinforcement.
- Anti rot and anti twist.
- Hose with couplings are wound by Galvanized mild steel/SS wire.

APPLICATIONS

- Industrial and rural fire brigades as well as building protection.
- For general industrial, commercial and civil engineering applications.

HOSE DATA

Hose : Type 2
 Available Color : Red, White
 Standard Length : 25/30 Meters

SPECIFICATION

Model Number	Diameter (in.)	Service Test Pressure (bar/psi)	Hydrostatic Strength Test Pressure (bar/psi)	Standard Compliance/ Approvals
NF-DH2-65R	2.5	15/215	50/725	BS 6391: 2009/ Kitemark& LPCB
NF-DH2-65W				

NH threaded. Storz & instantaneous coupling or other types are available upon request with approval.