

System Units NAFFCOInert, IG-541 engineered extinguishing system units, 200 or 300 bar

File Number: EX15844

COMPANY

NATIONAL FIRE FIGHTING MFG FZ CO

Po Box 17014 Jebel Ali Free Zone

JEBEL ALI FREE ZONE

Dubai, Dubai United Arab Emirates

SYSTEM UNITS INFO

NAFFCOInert, IG-541 engineered extinguishing system units, 200 or 300 bar

Engineered, Inert Gas

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	IG-541

MANUALS AND BULLETINS		
Part No.	Description	Date/Rev
027650015-NF	Engineered System Installation, Design and Maintenance Manual	Rev. 11 dated December 2021

SYSTEM UNIT INFORMATION		
Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
200 bar at 21 °C	-20 C (-4 F)	65 C (149 F)
300 bar at 21 °C	-20 C (-4 F)	65 C (149 F)

THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:
Software Name/Version
VDS SCHADENVERHUTUNG Engineered System Flow Calculation Software Version 2.01



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."