

Security Rated Door

The SR2 range of security doors consists of both single and double door-sets made of steel that have been rated for security, and are intended for use in places that could benefit from increased protection. When there is a heightened risk of forced entry by intruders, SR2 doors are appropriate for facilities that demand a greater degree of security protection. The dorset is attacked with a variety of hand tools for a maximum of 15 minutes, with a maximum working time of 3 minutes.



- Schools
- Universities
- Housing association communal areas
- Leisure facilities
- Retail Outlets

Features and Benefits

- Tested to LPS1175 SR2 standard.
- Mid-level security protection.
- Ideal for a wide variety of commercial and domestic premises.
- SR2 doors meets the specified time protection requirements of 3 minutes of continual attack.
- All double doorsets equipped with heavy duty barrel bolts as a standard feature.
- Wide variety of locking alternatives available for both single and double leaf doorsets.
- Heavy duty stainless steel hinges are used to hang all doors.

Optional

• Vision Panel

Certification

Certified by the Loss Prevention Certification Board to LPS 1175 Level 2 Issue 7 Cert/ LPCB Ref. 1542a





Specification

Door Type	Single and Double Door		
Security Rated	LPS 1175 Issue 7 SR2		
Fire Rating	1-4 hours subject to hardware and options selected		
Material	Galvanised or Zintec Steel dependent on door size and type		
Door leaf thickness	52mm		
Sheet thickness of Door leaf	1.0 – 1.25mm		
Sheet thickness of door frame	1.5mm		
Burglary resistance	Single leaf BR RC 2 NS EN1627 Double leaf BR RC 2 NS EN1627		
Acoustic rating	Up to 41dB		
Finish	Many finish options are available, including powder coating in various RAL colors.		

Door Sizes

all measurements are in millimeters (mm)

	Min. Width	Max. Width	Min. Height	Max. Height
Single Door	600	1440	1800	3100
Double Door	1100	2800	1800	3100