

Security Rated Door

Secura³

The SR3 range of security doors consists of both single and double door-sets made of steel that have been rated for security, and are intended for use in places that could benefit from increased protection. When there is a heightened risk of forced entry by intruders, SR3 doors are appropriate for facilities that demand a greater degree of security protection. The doorset is attacked with a variety of hand tools for a maximum of 15 minutes, with a maximum working time of 5 minutes.

Application

- Banks
- Retail Outlets
- Ministry of Defense
- Police Stations
- Cash Offices
- Hospitals
- Utility Buildings

Features and Benefits

- Tested to LPS1175 SR3 standard.
- Mid-level security protection.
- Ideal for a wide variety of commercial and domestic premises.
- SR3 doors meets the specified time protection requirements of 5 minutes of continual attack.
- All double doorsets equipped with independent hooked dog bolts at top and bottom of door leaf.
- SR3 doors offer moderate security and are designed to resist determined attempts at forced entry using physical force and a wide range of hand tools.
- Doors are hung with tough recessed stainless steel hinges that feature anti-crushing fixtures.

Optional

- Vision Panel

Certification

Certified by the Loss Prevention Certification Board to LPS 1175 Level 3 Issue 7 Cert/
LPCB Ref. 1542a



Specification

Door Type	Single and Double Door
Security Rated	The LPS 1175 Issue 7 SR3
Fire Rating	1-4 hours subject to hardware and options selected
Material	Galvanised or Zintec Steel dependent on door size and type
Door leaf thickness	52mm
Sheet thickness of Door leaf	1.25mm
Sheet thickness of door frame	1.5mm
Burglary resistance	Single leaf BR RC 3 NS EN1627 Double leaf BR RC 3 NS EN1627
Acoustic rating	Up to 41dB
Finish	Many finish options are available, including powder coating in various RAL colors.

Door Sizes

all measurements are in millimeters (mm)

	Min. Width	Max. Width	Min. Height	Max. Height
Single Door	600	1430	1750	2930
Double Door	1000	2600	1750	2930