





NAFFCO reserve the right to introduce minor changes to improve operational and performance related aspects of the vehicle and if also necessary to supply equivalent equipment/components if they should become unavailable or obsolete.







## **NAFFCO**

**BODY STRUCTURE** 

UV stabilized Polypropylene structure

**FOAM SYSTEM** 

• NAFFS-AATP

• Foam ratios: 0-6%

• UL classified as per NFPA 1901

• Electronic operated control system

**ELECTRIC WINCH** 

• 12000 lbs. / 5443 kg Pulling rate

STORAGE COMPARTMENT CHASSIS • Four (4) capacity lockers,

 MB Arocs • 33,300 kg GVW, 6x4

• 421HP @ 2200 RPM, Euro 3

**WATER/FOAM TANKS** 

· Poly Propylene (PP)

• Water 3,000 liters

• Foam 4,000 liters

· Lifetime warranty

**ELECTRICAL SYSTEM** 

Beacon lights

 Flash lights · Search light with

Extendable pole

• Side Illumination lights

• Side Illumination lights

· HMI display at driver cabin

· Touch display at pump control panel

**NAFFCO CREW CAB** 

· GRP material

 Accommodates 4 passengers with SCBA seats

**WATER PUMP** 

• Stainless steel material

• Dust and waterproof

· Light alloy roller shutter

• Automatic Priming System

• 4000 LPM @ 12 Bar, Centrifugal type

• Two (2) Hose reel: 1" x 25m

Two (2) on LH and RH sides

**ROOF MONITOR** 

• 4,000 LPM @ 8 Bar

 Horizontally 360° / Vertically +100° & -15°

• Electronic operated control system

**ACCESSORIES/TOOLS** 

• Wide range of rescue and firefighting equipment/tools

• Standard tools can be provided.













