

NAFFCO reserve the right to introduce minor changes to improve operational and performance related aspects of the vehicle and if also necessary to supply equivalent equipment/components if they should become unavailable or obsolete.

8 0 0 - 6 2 3 3 2 6 customerservice@naffco.com FOR OUTSIDE UAE, PLEASE CALL +971 800 623 326

www.naffco.com

Ø

f

y

NAFFCO

01 CHASSIS

- MAN TGM 18.290
- 18,000 kg GVW, 4x4
- Engine 213kw (290HP) Euro 4
- Six (6) No. SCBA seats
- Reached up to 6 passengers

BODY STRUCTURE

- Aluminium profiles 6061 T6 structure
- Stainless steel tubing base structure

(3) STORAGE COMPARTMENT

- Four(4) capacity lockers, Two(2) on LH and RH sides
- Dust and waterproof
- Light alloy anodized roller shutter

• FIRE PUMP

- Normal Pressure Centrifugal Pump
- Automatic Priming System
 3000 LPM @ 10 Bar

FOAM PUMP

- Bronze material220 LPM @ 15 Bar
- Gear Pump
- Gear Puni

06

FOAM SYSTEM

Naffco balance pressure system
Foam ratios: 0%, 3% & 6%

WATER/FOAM TANKS

- Poly Propylene (PP)
- Water 6,000 liters
- Foam 500 liters
- Lifetime warranty

ELECTRICAL SYSTEM

- Separately fused electrical circuits
- Light bar with PA system











ACCESSORIES Wide range of firefighting accessories and rescue tools.