

# NFM 40/4-SC Light Duty Firefighting Vehicle

### **CHASSIS**

MAN TGL 12.180, 4x2, Single Cabin, Manual Transmission, 180 HP. 11.900 KG GVW

### **BODY STRUCTURE**

Made using aluminum profiles 6061 T6, fastened to a strong base structure made of stainless steel tubing

### STORAGE LOCKERS

Five (5) storage lockers, two on the R/H side and two on the L/H side and one on the rear of the vehicle closed by light alloy roller shutters.

### **WATER & FOAM TANKS**

4,000/400 Liters made of Polypropylene with life time warranty

### **FIRE PUMP**

PTO Driven, Single stage, centrifugal type normal pressure pump, 2,000 LPM at 10 bar and 3 meter suction lift.

### **FOAM SYSTEM**

Around-the-Pump-Foam Proportioning System 0 - 6 %, Manual adjustable

# APPROX.43-30 STREET SIDE VEW REAR SIDE VEW

CURB SIDE VIEW

FRONT SIDE VIEW

## **MONITOR**

Water / Foam Monitor with jet/fog pattern, with adjustable output from 800 LPM to 1,600 LPM and throw range up to 50 meters

### **HOSE REEL**

Manual Rewind hose reel fitted with rubber hose of 1.25" x 30m fitted with pistol type nozzle for jet and fog patterns.

### **ACCESSORIES**

Wide range of fire fighting accessories and equipments including hoses, nozzle, SCBA Sets, Generator and personal fire protection sets.





### Notes:

NAFFCO reserve the right to introduce minor changes to improve operational and performance related aspects of the vehicle and if also necessary to supply equivalent equipment/components if they should become unavailable or obsolete.